




Silový kleštinový upínač

High performance milling chuck HKS-system



pro upínací stopky DIN 1835 A+B+E a DIN 6535 HA+HB+HE
for mounting straight-shank tools acc.



Katalogové číslo Catalog number	Kužel Taper	Rozsah Capacity	D	d	A			G 6,3 15.000 min ⁻¹
BT40.90.S.20.ADB	BT40	3 - 20 (RS20)	53	20	90	AD/B	RS20K	•
BT40.90.S.25.ADB	BT40	3 - 25 (RS25)	63	25	90	AD/B	RS32K	•
BT40.90.S.32.ADB	BT40	3 - 32 (RS32)	68	32	90	AD/B	RS32K	•
BT50.95.S.20.ADB	BT50	3 - 20 (RS20)	53	20	95	AD/B	RS20K	•
BT50.95.S.25.ADB	BT50	3 - 25 (RS25)	63	25	95	AD/B	RS32K	•
BT50.90.S.32.ADB	BT50	3 - 32 (RS32)	68	32	90	AD/B	RS32K	•

dodávka: s vyváženou upínací maticí, bez montážního klíče
delivery: with balanced clamping nut, without wrench

Velikost Size	20 mm	25 mm	32 mm
Upínací moment Clamping torque	50 - 70 Nm	80 - 100 Nm	80 - 100 Nm
Upínací síla Clamping force	780 Nm	2000 Nm	2000 Nm