



Silový kleštinový upínač

High performance milling chuck HKS-system



pro upínací stopky DIN 1835 A+B+E a DIN 6535 HA+HB+HE
for mounting straight-shank tools acc.



Název Catalog number	Kužel Taper	Rozsah Capacity	D	d	A		G 6,3 15.000 min ⁻¹
HSK63A.95.S.20	HSK63A	3 - 20 (RS20)	53	20	95	RS20K	•
HSK63A.100.S.25	HSK63A	3 - 25 (RS25)	63	25	100	RS25K	•
HSK63A.110.S.32	HSK63A	3 - 32 (RS32)	68	32	110	RS32K	•
HSK100A.105.S.20	HSK100A	3 - 20 (RS20)	53	20	105	RS20K	•
HSK100A.105.S.25	HSK100A	3 - 25 (RS25)	63	25	105	RS25K	•
HSK100A.105.S.32	HSK100A	3 - 32 (RS32)	68	32	105	RS32K	•

dodávka: bez montážního klíče

delivery: without wrench

Velikost Size	20 mm	25 mm	32 mm
Upínací moment Clamping torque	50 - 70 Nm	80 - 100 Nm	80 - 100 Nm
Upínací síla Clamping force	780 Nm	2000 Nm	2000 Nm