


Kleština RH_B pro hydro-upínače

Reduction sleeves for hydraulic expansion chucks for internal coolant supply



pro vnitřní chlazení do 80 barů
coolant proof up to max. 80 bar




obvodové házení $\leq 0,005$
radial run-out $\leq 0,005$

Název Catalog number	d	D	L
RH20TB D..	3, 4, 5, 6, 8, 10, 12, 14, 16	20	52,9
RH25TB D..	3, 4, 5, 6, 8, 10, 12, 14, 16, 18, 20	25	52,5
RH32TB D..	3, 4, 5, 6, 8, 10, 12, 14, 16, 18, 20, 25	32	66

poznámka: pro upínání hladké stoky v toleranci h6
note: the chucking diameter is configured for a tool tolerance of h6

Kleština RH pro hydro-upínače

Reduction sleeves for hydraulic expansion chucks with peripheral cooling, collar slotted, not coolant proof



obvodové házení $\leq 0,005$
radial run-out $\leq 0,005$

Název Catalog number	d	D	L
RH20 D..	3, 4, 5, 6, 8, 10, 12, 14, 16	20	53
RH25 D..	3, 4, 5, 6, 8, 10, 12, 14, 16, 18, 20	25	60
RH32 D..	6, 8, 10, 12, 14, 16, 18, 20, 25	32	64,6

poznámka: pro upínání hladké stoky v toleranci h6
note: the chucking diameter is configured for a tool tolerance of h6