




# Silový kleštinový upínač

## High performance milling chuck HKS-system



pro upínací stopky DIN 1835 A+B+E a DIN 6535 HA+HB+HE  
for mounting straight-shank tools acc.



Název Catalog number	Kužel Taper	Rozsah Capacity	D	d	A			G 6,3 15.000 min <sup>-1</sup>
SK40.90.S.20.ADB	SK40	3 - 20 (RS20)	53	20	90	AD/B	RS20K	•
SK40.105.S.25.ADB	SK40	3 - 25 (RS25)	63	25	105	AD/B	RS32K	•
SK40.105.S.32.ADB	SK40	3 - 32 (RS32)	68	32	105	AD/B	RS32K	•
SK50.90.S.20.ADB	SK50	3 - 20 (RS20)	53	20	90	AD/B	RS20K	•
SK50.90.S.25.ADB	SK50	3 - 25 (RS25)	63	25	90	AD/B	RS32K	•
SK50.90.S.32.ADB	SK50	3 - 32 (RS32)	68	32	90	AD/B	RS32K	•

dodávka: s vyváženou upínací maticí, bez montážního klíče

delivery: with balanced clamping nut, without wrench

<b>Velikost</b> Size	20 mm	25 mm	32 mm
<b>Upínací moment</b> Clamping torque	50 - 70 Nm	80 - 100 Nm	80 - 100 Nm
<b>Upínací síla</b> Clamping force	780 Nm	2000 Nm	2000 Nm